

Tri-Wing

A flex mower specifically designed for large open spaces, with wide-angle constant velocity drive shafts and in-line slip clutch protection.

The clean lines of this robust design, reduces the build up cut debris from collecting and rotting the machine deck, maximising it's working life.

Fitted with six 200/60 - 14.5 10 ply tyres as standard, the Tri-Wing 4.6 and 6m can also be supplied with an eight wheel option for reduced ground pressure. The sprung shock absorbing mechanism ensures a smooth ride and reduces stress within the mainframe.

Key Features

- 4.6m and 6m cutting widths
- Walking wheel kit option
- Nine heavy duty updraft blades
- Choice of 5 blade configurations
- Shredder option for maize
- Sprung suspension system
- 2.3m and 2.6m transport widths
- Hydraulic level lift system



Want to know more about the Tri-Wing range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: www.bomford-turner.com/landscape/flail-mowers-and-toppers/tri-wing/



Product Specification

Tri-Wing	TW4600	TW6000
Cutting Width	4.60m / 15'	6.00m / 20'
Overall Width	4.75m / 15'7"	6.30m / 20'8"
Overall Length	4.47m / 14'8"	5.15m / 16'11"
Transport Width	2.34m / 7'8"	2.55m / 8'4"
Cutting Height	25mm - 375mm / 1" - 15"	25mm - 375mm / 1" - 15"
Horsepower (min)	80hp	100hp
Blade Overlap	150mm / 6"	150mm / 6"
PTO Speed	1000	1000
Wing Flex (Degrees)	90° up - 22° down	90° up - 22° down
Weight (Approx)	2420kg / 5335lbs	3470kg / 7650lbs



Road lights

High speed road lighting and licence plate brackets.



Axle options

Walking axle options for contour following operation.



Contoured decks

Allows quick cleaning of cut material from deck surface.



Easy to Transport

Simple single operation to fold and travel, with additional locking pins for road transit.



Wide Coverage

4.6m and 6.0m models allow wide cutting passes to tackle large open areas quickly.