



# TLBE-SG

HYDRAULIC MULCHING HEAD  
WITH SWIVEL (180°)  
(for excavator)



[www.lipa-srl.it](http://www.lipa-srl.it)  
[info@lipa-srl.it](mailto:info@lipa-srl.it)

65010 Spoltore (PE) - Italy  
Via Castellani (ang. Via Mare Adriatico)  
Tel. +39 085 4971431 Fax +39 085 4973170

# TLBE-SG

HYDRAULIC  
MULCHING HEAD  
WITH SWIVEL (180°)  
(for excavator)



## STANDARD EQUIPMENT

- attachment saddle (25kg)
- saddle adjustment rail
- hydraulic gear motor group 3
- 180° swivel fifth wheel
- anti-cavitation valve
- belt transmission
- rotor with toothed hammers and oversized supports
- internal counterframe
- double series of counter-elements
- front protection with galvanised and rubber chain
- rear rubber protection
- pair of skids
- rear height-adjustable roller with scraper
- special powder or liquid painting (primer and enamel)

The TLBE-SG mulching head is ideal for the mulching of grass, reeds and bushes up to a maximum of 7/8 cm in diameter, near ditches, embankments and on all steep slopes. Application of the 180° rotating fifth wheel means being able to work while optimising operating times and increasing productivity. Fits excavators weighing up to 5 t.

Mod.									
	B	L	* Kg	(g/min.)	L/1* *	Press. BAR	D. Rotor		
<b>TLBE-SG 90</b>	1050	940	440	2300	45/55	220/250	7	140	3
<b>TLBE-SG 100</b>	1150	1040	450	2300	50/60	220/250	7	140	3
<b>TLBE-SG 110</b>	1250	1140	470	2300	60/70	220/250	8	140	3
<b>TLBE-SG 120</b>	1350	1240	490	2300	60/70	220/250	8	140	3

\* The data shown in the table are indicative, refer to the weight of the mulching head without saddle and the litres are those required by the shredding head for its operation.

## ACCESSORIES ON REQUEST

1. Oscillating attachment (50 kg)
2. Saddle fixing pins
3. Surcharge valve block with flow and limiter regulator
4. There is an additional cost for customising of the saddle



The technical data, illustrations and features are indicative and do not commit the manufacturer (put at the end of the page)